



Technical data

1. Nominal voltage: 150V/4A  
Pitch: 2.5mm
2. Insulation Withstands Voltage:  
AC1300V/MIN
3. Insulation Resistance:  
1000MΩ or more at DC500V
4. Using temperature range: -40°C ~ 115°C
5. Soldering temperature range: 250°C ± 10°C / 5sec
6. Safety approval:
7. RoHS Compliance
8. Critical dimension:
9. Undimensioned Tolerances:

Dim L=(P-1)X2.5+4.4	Dim B	Dim L
Dim B=(P-1)X2.5	±0.15	±0.20
P = number of poles	±0.20	±0.25
0-30mm	±0.25	±0.30
over 30mm-60mm	±0.30	±0.40
over 60mm-90mm		
over 90mm		

HABH250 xx x xxx

- ① Colors 02-24
- ② Color  
0 Black 3 Orange 5 Green 6 Blue.....
- ③ Custom  
000 K MARK 00K KUNACON MARK.....

2	PIN	COPPER	TIN PLATED	P					
1	BODY	PA66 UL94V-0		1					
ITEM NAME OF PART MATERIAL NOTES									
DWG	WF. Zhang	DATE	2016.03.10	UNITS	MM	SHEET	1 OF 1	Tolerance	±0.50
CHK.	WF. Zhang	DATE	2016.03.10	SCALE:	NONE 4:1 ( : )	REV.:	A		±0.30
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-BH250 Series Close type X X Right angle(90D)				±0.10
PART NO.		HABH250xxxxxx			PART NO.		HA-B250-B001		
DWG NO.		HA-B250-B001			DWG NO.		HA-B250-B001		
SIGN		DESCRIPTION			CHK.		DATE		
A									



KUNA Contact Technology Co. Ltd  
http://www.kunacon.com