



Technical data

- 1.Nominal voltage: 150V/4A
- PITCH:2.5mm
- 2.Insulation Withstands Voltage: AC1300V/MIN
- 3.Insulation Resistance: 1000M Ω or more at DC500V

4.Using temperature range:-40C ~ 115C°

5.Soldering temperature range:250C° \pm 10C°/5sec

6.Safety approval:

7.RoHS Compliance

8.Critical dimension:

9.Undimensioned Tolerances:

Dim.L=(P-1)X2.5+4.4	Dim B	Dim L
Dim.B=(P-1)X2.5	0-30mm	± 0.15
P = number of poles	over 30mm-60mm	± 0.20
	over 60mm-90mm	± 0.25
	over 90mm	± 0.30
		± 0.40

HABV250 xx x xxx

- ① Poles 02-24
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue.....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

2	PIN	COPPER	TIN PLATED	P						
1	BODY	PA66 UL94V-0		1						
MATERIAL										
DWG.	WF. Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	NOTES	1 OF 1	Tolerance
CHK.	WF. Zhang	DATE	2016.03.10	SCALE:	NONE 4:1 (:)	REV.:	A			X
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-BV250 Series Close type					X
					Vertical(180D)					X
				PART NO.	HABV250xxxxxx					X*
				DWG NO.	HA-B250-B002					$\pm 1^{\circ}$

△	SIGN	DESCRIPTION	CHK.	DATE
---	------	-------------	------	------



KUNA Contact Technology Co. Ltd
http://www.kunacon.com