



Technical data  
 1.Nominal voltage: 300V/8A  
 PITCH:3.5mm

2.Insulation Withstands Voltage:  
 AC1600V/MIN

3.Insulation Resistace:  
 1000MΩ or more at DC500V

4.Using temperature range:-40°C ~115°C

5.Soldering temperature range:250°C±10°C/5sec

6.Safety approval:

7.RoHS Compliance

8.Critical dimension:

9.Undimensioned Tolerances:

Dim L=(P-1)X3.5+4.4	Dim B	Dim L
Dim B=(P-1)X3.5	±0.15	±0.20
P= number of poles	±0.20	±0.25
0-30mm	±0.25	±0.30
over 30mm-60mm	±0.30	±0.40
over 60mm-90mm		
over 90mm		

HADH350 xxx x xxx

① Poles 02-24

② Color

0 Black 3 Orange 5 Green 6 Blue.....

③ Custom 000 K MARK 00K KUNACON MARK.....

2	PIN	BRASS	TIN PLATED	P				
1	BODY	PA66 UL94V-0		1				
MATERIAL								
DWG	WF. Zhang	DATE	2016.03.10	UNITS:	MM	SHEET:	1 OF 1	Tolerance
CHK.	WF. Zhang	DATE	2016.03.10	SCALE:	NONE 4:1 ( : )	REV.:	A	±0.50
APP.	Marvin Zhang	DATE	2016.03.31	TITLE:	HA-DH350 Series Latch type			±0.30
					Right-angle(90D)			±0.10
				PART NO.:	HADH350xxxxxx			±1°
				DWG NO.:	HA-D350-B002			

△	SIGN	DESCRIPTION	CHK.	DATE



KUNA Contact Technology Co. Ltd  
<http://www.kunacon.com>