


Technical data

1. Nominal voltage: 150V/8A  
PITCH: 3.5mm
  2. Insulation Withstands Voltage:  
AC 1300V/MIN
  3. Insulation Resistance:  
1000M $\Omega$  or more at DC500V
  4. Using temperature range: -40C $^{\circ}$ -115C $^{\circ}$
  5. Undimensioned Tolerances:  
Dim L = (P-1)X3.5+5.0  
Dim B = (P-1)X3.5  
P = 1/2 Number of poles (04-48P)
- |                | Dim B      | Dim L      |
|----------------|------------|------------|
| 0-30mm         | $\pm 0.15$ | $\pm 0.20$ |
| over 30mm-60mm | $\pm 0.20$ | $\pm 0.25$ |
| over 60mm-90mm | $\pm 0.25$ | $\pm 0.30$ |
| over 90mm      | $\pm 0.30$ | $\pm 0.40$ |
6. Safety approval:
  7. RoHS Compliance
  8. Critical dimension:
- HFBH350 xxx x xxx**
- ① Poles 04-48(2 $\times$ 02-2 $\times$ 24)
  - ② Color
  - 0 Black 3 Orange 5 Green 6 Blue G-Pale gray....
  - ③ Custom
  - 000 K MARK 00K KUNACON MARK....



ITEM	NAME OF PART	MATERIAL	NOTES	QTY
3	PIN 2	COPPER	TIN PLATED	1/2P
2	PIN 1	COPPER	TIN PLATED	1/2P
1	BODY	PA66 UL94V-0	ALL COLOR	1

DWG. W/F.	DATE	UNITS	MM	SHEET	1 OF 1	Tolerance
Zhang	2016.03.10	NONE	2.5:1 (.)	REV. A		$\pm 0.50$
W/F. Zhang	2016.03.10	SCALE:				$\pm 0.30$
APP. Marvin Zhang	2016.03.31	TITLE:				$\pm 0.10$

Part No. HFBH350xxxxxx  
Title: HF-BH350 Series Close type Right angle (90D)

PART NO.	DWG NO.	QTY
HFBH350xxxxxx	HF-B350-B001	1

KUNA Contact Technology Co. Ltd  
http://www.kunacon.com

SIGN	DESCRIPTION	CHK.	DATE