



**Technical data**

- 1. Nominal voltage: 150V/8A  
PITCH: 3.5mm
- 2. Insulation Withstands Voltage:  
AC 1300V/MIN
- 3. Insulation Resistance:  
1000M $\Omega$  or more at DC500V
- 4. Using temperature range: -40C°-115C°
- 5. Undimensioned Tolerances:

Dim L = (P-1)X3.5+5.0	Dim B	Dim L
Dim B = (P-1)X3.5	0-30mm	±0.15
P=1/2 Number of poles (04-48P)	over 30mm-60mm	±0.20
	over 60mm-90mm	±0.25
	over 90mm	±0.30
		±0.40

- 6. Safety approval:
- 7. RoHS Compliance
- 8. Critical dimension:
- HFBV350 xxx X xxxx
- ① Poles 04-48(2x02-2x24)
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue G Pale gray.....
- ③ Custom
- 000 K MARK 00K KUNACON MARK.....

2	PIN	COPPER	TIN PLATED	P
1	BODY	PA66 UL94V-0	ALL COLOR	1
MATERIAL				
DWG. W/F. Zhang	DATE 2016.03.10	UNITS: MM	SHEET: 1 OF 1	Tolerance
CHK. W/F. Zhang	DATE 2016.03.10	SCALE: NONE 2.5:1 (.)	REV.: A	X ±0.50
APP. Marvin Zhang	DATE 2016.03.31	TITLE: HF-BV350 Series Close type X.XX	Vertical (180D)	X.XX ±0.30
		PART NO. HFBV350xxxxxx		X.XX ±0.10
		DWG NO. HF-B350-B002		X <sup>+</sup> ±1 <sup>+</sup>
KUNA Contact Technology Co. Ltd http://www.kunacon.com				
△	SIGN	DESCRIPTION	CHK.	DATE