



Technical data

- 1. Nominal voltage: 150V/8A
Pitch: 3.81mm
- 2. Insulation Withstands Voltage:
AC 1300V/MIN
- 3. Insulation Resistance:
1000M Ω or more at DC500V
- 4. Using temperature range: -40C \circ -115C \circ
- 5. Undimmed stoned Tolerances:

| | | |
|-------------------------------|----------------|------------|
| Dim L = (P-1)X3.81+4.4 | Dim B | Dim L |
| Dim B = (P-1)X3.81 | ± 0.15 | ± 0.20 |
| P=1/2 Number of poles (4-48P) | over 30mm-60mm | ± 0.25 |
| | over 60mm-90mm | ± 0.30 |
| | over 90mm | ± 0.40 |

- 6. Safety approval:
- 7. RoHS Compliance
- 8. Critical dimension:

HFDH381 XX XXX
 ① Poles 04-48(2x02-2x24)
 ② Color
 0 Black 3 Orange 5 Green 6 Blue G Pale Gray....
 ③ Custom
 000 K MARK 00K KUNACON MARK....

| | | | | | | | | |
|-------------------|--------------|---------------|------------|--------|---|--------|-----------------|-----------|
| 3 | PIN 2 | COPPER | TIN PLATED | 1/2P | | | | |
| 2 | PIN 1 | COPPER | TIN PLATED | 1/2P | | | | |
| 1 | BODY | PA66 UL94V-0 | ALL COLOR | 1 | | | | |
| ITEM NAME OF PART | | | | | | | | |
| DWG. | WF. Zhang | DATE | 2016.03.10 | UNITS: | MM | SHEET: | 1 OF 1 | Tolerance |
| CHK. | WF. Zhang | DATE | 2016.03.10 | SCALE: | NONE 2.5:1 (.) | REV.: | A | X |
| APP. | Marvin Zhang | DATE | 2016.03.31 | TITLE: | HF-DH381 Series with engagement nose type 90D | | | |
| PART NO. | | HFDH381XXXXXX | | | X | | X | |
| DWG NO. | | HF-D381-B001 | | | X* | | ±1 ^o | |

| | | | | |
|---|------|-------------|------|------|
| △ | SIGN | DESCRIPTION | CHK. | DATE |
|---|------|-------------|------|------|

