



Technical data

- 1.Nominal voltage: 300V/20A
PITCH:5.08mm
- 2.Connection capacity:
AWG 30-12
- 3.Insulation Withstanding Voltage:
AC 1600V/MIN
- 4.Insulation Resistance:
1000MΩ or more at DC500V
- 5.Tightening torque:
4.3lb-In(5.0kgf.cm / 0.5N.m)
- 6.Screw thread: M3
- 7.Stripping length: 7-8mm
- 8.Using temperature range:-40C°-115C°
Soldering temperature:250±10C°/5s
- 9.Undimensioned Tolerances:

Dim.L=P×5.08	Dim B	Dim L
Dim.B=(P-1)×5.08	±0.15	±0.20
P = number of poles (02-24P)	over 30mm-60mm	±0.20
	over 60mm-90mm	±0.25
	over 90mm	±0.30
		±0.40

- 10.Safety approval:
- 11.RoHS Compliance:
- 12.Critical dimension:

- ① Poles 02-24
- ② Color
- 0 Black 3 Orange 5 Green 6 Blue G Pale gray.....
- ③ Custom
- A00 K MARK A0K KUNACON MARK.....

4	CONTACT	BRASS	Tin PLATED	P				
3	SCREW	STEEL	M3×0.5, Ni Plated	P				
2	CAGE	BRASS	M3×0.5, Ni PLATED	P				
1	BODY	PA66 UL94V-0	ALL COLOR	1				
ITEM NAME OF PART								
MATERIAL								
DWG.	WF. Zhang	DATE	2018.10.12	UNITS:	MM	SHEET:	1 OF 1	Tolerance
CHK.	WF. Zhang	DATE	2018.10.12	SCALE:	NONE 3:1 (.)	REV.:	A	
APP.		DATE		TITLE:	EJ-H508 Series 2-Interlock			
					180D " " Slot Screw A type			
				PART NO.:	EJHM508XXXXA0X			
				DWG NO.:	EJ-H508-B201			
					X			±0.50
					X X			±0.30
					X X X			±0.10
					X*			±1*

REV	SIGN	DESCRIPTION	CHK.	DATE
Δ				



KUNA Contact Technology Co. Ltd
http://www.kunacont.com